

MAG6588 Intelligent Network Paging Station



คุณลักษณะทั่วไป

- เป็นไมโครโฟนควบคุมและสั่งงาน ประกาศโดยระบบ Network
- หน้าจอสี 7 นิ้ว Touch Screen Control
- มีช่องต่อสัญญาณขาเข้าแบบ Line , ขาออกแบบ AUX และ NET พร้อมกับช่องต่อหูฟัง
- รองรับ TCP/IP
- สามารถตรวจเช็คข้อมูลโซนได้ทั้งหมด
- ล็อคการจัดการระบบทั้งหมด และปรับหน้าจอ Screen ได้
- สามารถขยายโซนได้สูงถึง 1,000 โซน

คุณลักษณะเฉพาะ

- AUX OUT Rated Output Voltage: 1.0±0.2V
- NET OUT Rated Output Voltage: 1.0±0.2V
- MIC input sensitivity (1V output): 50±10mV
- MIC distortion (1kHz/1V): MIC: ≤0.3%
- Effective frequency of MIC gain limit (±3dB): 100-16000Hz
- MIC Signal to Noise Ratio (30K lowpass): ≥68dB
- MIC dynamic range: ≥20dB
- AUX input sensitivity (1V output): 300±50mV



MAKE IT LOUD

Razr
SOUND SYSTEM

- AUX distortion (1kHz/1V): AUX≤0.3%
- AUX dynamic range: ≥20dB
- AUX Signal to Noise Ratio (30K lowpass): ≥68dB
- Effective frequency of AUX gain limit (±3dB): 50-18000Hz
- Effective frequency of monitoring (talkback voice) gain limit (±3dB): 80-16000 Hz
- Monitoring SNR (talkback voice): ≥65dB
- Working voltage: DC+14V
- Standby power consumption: 7.3W
- Power supply: AC220V/50Hz
- Overall power consumption: 9.5W
- Package dimensions (L×W×H mm): 415×280×121mm
- Machine dimensions (L×W×H mm): 300×160×56mm
- Gross weight: 2.5kg
- Net Weight: 1.8kg



CHINAVUT MARKETING CO., LTD.

63,65,67 Soi Rungruang , Ratchadapisek Rd., Samsaennok , Huay-Kwang Bangkok 10320
Tel : 0-2694-3000 , Email : info@chinavut.com , Website : www.chinavut.com

Razr Board

Razr Projection Screen

Razr SOUND SYSTEM